

**Trim Black (Aerosol)**

**SXA9000**

**SXA9000 Trim Black** is formulated to match the OEM finish on automotive exterior trim components. It provides excellent adhesion and flexibility when used on most plastics, steel, aluminum, stainless steel and chrome. It is packaged in a 20 ounce aerosol container.



**Features**

- Excellent adhesion
- Great coverage

**Advantages**

- No primer required
- Matches OEM finishes

**Benefits**

- Professional results

**Required Products**

- SXA9000 Trim Black

**Compatible Substrates**

- Exterior trim parts
- Properly prepared substrates including plastic, steel, aluminum, stainless steel and chrome

**Directions for Use**

**Surface Preparation:**



Ensure surface area is properly cleaned, removing all surface contaminants.  
Follow application instructions and observe proper flash and dry times.

**Mixing:**



SXA9000 is a ready-to-spray aerosol.  
Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to ensure color uniformity and to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).

**Directions for Use continued**

**Application:**



**Step 1:** Apply 1 – 2 coats of SXA9000 Trim Black

**Step 2:** Allow 2 -3 minute flash between coats @ 70°F (20°C)

**Tips for Success:**

- When applying product, hold the aerosol can upright 8 – 10 inches from the surface area and apply with uniform application coats.
- For best results, spray a test panel before applying to prepared substrate.

**Note:** *If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.*

**Dry Times:**

Flash Between Coats	2 – 3 minutes @ 70°F (20°C)
Dust free	5 minutes @ 70°F (20°C)

**Technical Data:**

Color	Black
Aerosol Coating Category:	Automotive Bumper and Trim Product
Aerosol Category Reactivity Limit	1.75
Package VOC (lbs/gal)	5.43
Total Solids by Weight	8.1%
Total Solids by Volume	5.0%
Sq. Ft. Coverage/US Gal. (1 mil 100% transfer efficiency)	80
Recommended Dry film	0.3 mil

**Important:**

Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

**Tips:**

- Do spray product in properly vented areas.
- Do use the appropriate NIOSH/MSHA respirator. Consult product label for details.
- Do shake for one minute after mixing ball rattles and spray a small area to test product before starting the job.
- Do turn the container over and spray to clear the nozzle after spraying is completed.

**Precautions:**

- Do not leave or store containers in direct sunlight. Normal storage temperature is 50°F – 100°F (50°C – 38°C).
- Do not incinerate container, contents under pressure.

**See material Safety Data Sheet and Labels for additional safety information and handling instructions.**

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434 -4515. IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.

# PPG Industries

*World Leaders in Automotive Finishes*

PPG Industries  
19699 Progress Drive  
Strongsville, OH 44149  
1-800-647-6050

PPG Canada Inc.  
2301 Royal Windsor Drive  
Mississauga, Ontario, Canada L5J 1K5  
1-888-310-4762