



RTS Combinations:	JP252 : JR555 : JH353	JP252 : JR555 : JH353
Volume Ratio:	4 : 1 : 1	4 : 1/2 : 1
Applicable Use Category	Primer	Primer
VOC Actual (g/L)	140	152
VOC Actual (lbs/gal)	1.17	1.27
VOC Regulatory (less water less exempt) (g/L)	248	248
VOC Regulatory (less water less exempt) (lbs/gal)	2.07	2.07
Density (g/L)	1520	1535
Density (lbs/gal)	12.68	12.81
Volatiles wt. %	46.3	42.0
Water wt. %	0.0	0.0
Exempt wt. %	37.1	32.1
Water vol. %	0.0	0.0
Exempt vol. %	43.8	38.8

### Precautionary Information:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Follow label directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

### Medical Response:

**EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (304) 843-1300; IN CANADA (514) 645-1320.**

### Material Safety Data Sheet:

Material Data Safety Sheets for the PPG products mentioned in this publication are available through your PPG *Shop-Line*™ Distributor. To the best of our knowledge, the technical information in this bulletin is accurate; however, since PPG Industries is constantly improving its coating and paint formulas, the current technical data may vary somewhat from what was available when this bulletin was printed. Contact your *Shop-Line*™ Distributor for the most up-to-date information.